

PRODUCT DESCRIPTION: The Model DV is a hose-end drain valve that is designed for quick and easy draining of a piping system or component. The drain valve incorporates a mini-ball for on and off functioning, and has removable cap where a  $\frac{3}{4}$ " GHT hose can be connected. The drain valves are available in  $\frac{1}{4}$ " MNPT,  $\frac{1}{2}$ " MNPT, and  $\frac{3}{4}$ " MNPT end connections.

STANDARD MATERIAL SPECIFICATIONS			
Body	Brass		
Cap	Brass		
Cap Gasket	NBR Rubber		
Cap Strap	EPDM Dual Durometer Core		
Ball	Chrome Plated Brass		
Ball Seat	Teflon		
Handle	Plastic for 1/4", Chrome Plated Steel for 1/2" and 3/4"		
0 '6 '			

Specification information is provided to assist and is given without obligation or warranty. The Company reserves the right to make changes in design, materials, and/or specifications without notice or liability.

Phone: 972-271-8801

Fax: 972-271-8802


Form Number: SUBDV1

Revision 1 - 12/2011


## PRODUCT SPECIFICATIONS:

Maximum working pressure: 600 WOG / CWP
Maximum working temperature: -22°F to 250°F






1/4" HOSE-END DRAIN VALVE						
MODEL	Α	H1	H2	WEIGHT		
MV001	2.1	1.2	1.3	0.23		



½" HOSE-END DRAIN VALVE						
MODEL	Α	H1	H2	WEIGHT		
MV002	2.4	3.5	1.7	0.45		



¾" HOSE-END DRAIN VALVE						
MODEL	Α	H1	H2	WEIGHT		
MV003	2.5	3.5	1.7	0.50		

NOTE: All dimensions, weights, and materials are subject to minor variations. Consult with the factory for confirmation of dimensions, weights, and material specifications.

Phone: 972-271-8801

Fax: 972-271-8802